

DIN1481 Size (Diameter * Length)

Size	Size	Size	Size	Size
2x8	3.5x22	5x12	8x22	12x14
2x10	3.5x24	5x14	8x24	12x16
2x12	3.5x26	5x16	8x26	12x18
2x14	3.5x28	5x18	8x28	12x20
2x16	3.5x30	5x20	8x30	12x22
2x18	3.5x32	5x22	8x32	12x24
2x20	3.5x35	5x24	8x35	12x26
2.5x8	3.5x36	5x26	8x36	12x28
2.5x10	3.5x40	5x28	8x40	12x30
2.5x12	3.5x45	5x30	8x45	12x32
2.5x14	3.5x50	5x32	8x50	12x35
2.5x16	4x8	5x35	8x55	12x36
2.5x18	4x10	5x36	8x60	12x40
2.5x20	4x12	5x40	8x65	12x45
2.5x22	4x14	5x45	8x70	12x50
2.5x24	4x16	5x50	8x75	12x55
2.5x26	4x18	5x55	8x80	12x60
2.5x28	4x20	5x60	8x85	12x65
2.5x30	4x22	5x65	8x90	12x70
2.5x32	4x24	5x70	8x95	12x75
2.5x35	4x26	6x10	8x100	12x80
2.5x36	4x28	6x12	10x14	12x85
2.5x40	4x30	6x14	10x16	12x90
3x8	4x32	6x16	10x18	12x95
3x10	4x35	6x18	10x20	12x100
3x12	4x36	6x20	10x22	13x12
3x14	4x40	6x22	10x24	13x14
3x16	4x45	6x24	10x26	13x16
3x18	4x50	6x26	10x28	13x18
3x20	4.5x10	6x28	10x30	13x20
3x22	4.5x12	6x30	10x32	13x22
3x24	4.5x14	6x32	10x35	13x24
3x26	4.5x16	6x35	10x36	13x26
3x28	4.5x18	6x36	10x40	13x28
3x30	4.5x20	6x40	10x45	13x30
3x32	4.5x22	6x45	10x50	13x32
3x35	4.5x24	6x50	10x55	13x35
3x36	4.5x26	6x55	10x60	13x36
3x40	4.5x28	6x60	10x65	13x40
3x45	4.5x30	6x65	10x70	13x45
3.5x8	4.5x32	6x70	10x75	13x50
3.5x10	4.5x35	8x10	10x80	13x55
3.5x12	4.5x36	8x12	10x85	13x60
3.5x14	4.5x40	8x14	10x90	13x65
3.5x16	4.5x45	8x16	10x95	13x70
3.5x18	4.5x50	8x18	10x100	13x75
3.5x20	5x10	8x20	12x12	13x80

Size
13x85
13x90
13x95
13x100
14x18
14x20
14x22
14x24
14x26
14x28
14x30
14x32
14x35
14x36
14x40
14x45
14x50
14x55
14x60
14x65
14x70
14x75
14x80
14x85
14x90
14x95
14x100

Size
16x16
16x18
16x20
16x22
16x24
16x26
16x28
16x30
16x32
16x35
16x36
16x40
16x45
16x50
16x55
16x60
16x65
16x70
16x75
16x80
16x85
16x90
16x95
16x100

NAME: Spring Type Straight Pins, Slotted, Heavy Type

German standard:Tighter toleranc

Material: C67S or 65Mn high-quality

Surface: Black Phosphating Treatment

Type: normal type

hardness: HRC47-54 and Over 48mm in size_HRC44-51

